

Waterboy™ Wizard Trade Pack

The Waterboy™ Wizard Trade Pack consists of a Mains Water Switching Device and a Tank Pump Pressure Controller, supplied separately to avoid fitting manipulation during installation and to ensure leak-free operation. By following the simple installation instructions below, you will be able to construct the most efficient rainwater harvesting system on the market, seamlessly switching to mains water only when your tank runs dry without the need for an in-tank float.



1. Remove all packaging from the Mains Water Switching Device (A) and Tank Pump Pressure Controller (C)
2. Remove tape from the Mains Water Switching Device's Tank Pump Pressure Controller female fitting and ensure the O-ring (B) is greased
3. Firmly connect the Tank Pump Pressure Controller male fitting to the upper female fitting of a Waterboy Jet Pump that has been installed as detailed in the included instruction manual
4. Screw the Mains Water Switching Device's female fitting on to the Tank Pump Pressure Controller's male fitting and firmly tighten, ensuring the O-ring is correctly in position to create a water tight joint
5. Leak test all connections during initial operation
6. If a leak occurs between the Mains Water Switching Device and Tank Pump Pressure Controller, re-grease the O-ring and tighten firmly

NOTE: It is the responsibility of the installer to ensure the O-ring is installed correctly and the connection between the switching device and controller is water tight. A leaking joint as a consequence of incorrect or poor installation will not be covered under warranty

