

## AGA 8172 G

No curring required Non Toxic and non-flammable OK for Potable Water Not for Use on Plastic Piping

T-O-To is a Thix-O-Tropic compound that stays in a semi-solid state until the instant it is brushed on. Then it goes on smooth and easy. DIRECTIONS: Stir before using. Remove dirt or moisture from pipe threads. Then simply brush on LA-CO® 'T-O-T' on the threads of male fittings. Use on metal threads for water, steam, natural gas, LPG and air.



NON -TOXIC

BRUSH IN CAP





Temperature limitation, -10°C to 135°C Class I rated working pressure 20kPa When stored at 25°C in its original unopened container, LA-CO T.O.T. will retain its properties for a minimum period of two years.

## No Drip • No Spill • No Waste

- Siliconized for easy spreading Soft, fast and easy to apply Will not spill
- · Ends mess in tool boxes, trucks, job sites · Anti-seize prevents rust
- Lubricates for fast, easy makeup Permits easy disassembly years later Contains no lead • Non-toxic - non-hazardous to health • Non-hardening

LA-CO INDUSTRIES, INC. 1201 Pratt Boulevard, Elk Grove Village, IL 60007-5746 © 2020 LA-CO Industries, Inc. www.laco.com

Distributed by Bromic

10 Phiney Pl, Ingleburn NSW 2565 Australia bromicplumbing.com AUS: 1300 276 642 NZ: 0508 276 642

PP54R00349