

■ Contains no solvents ■ Easy disassembly and break out

Non-Flammable
AGA 8171G



LA-CO[®]

Clean and degrease sealing surfaces before application of sealant.
Not suitable for plastic pipes or fittings. Avoid contact with skin or eyes.

Meets ANSI LC7-2009 requirements. Working temp. range: 10°C to 135°C
CLASS II Rated working pressure 500kPa Use with natural gas & LP gases
(vapor state only). Use on steel, galvanized steel, iron, brass, copper &
aluminum. When stored at 25C in its original unopened container, LA-CO
Slic Tite will retain its properties for a minimum period of 2 yrs.

Slic-tite[®]

PP52R02105

PASTE WITH PTFE

Heavy Duty Thread Sealing Compound

BRUSH IN CAP
NON-TOXIC

Use for threaded connections on steel, aluminum, brass, PVC, CPVC and ABS.
WORKING PRESSURES: To 10,000 psi-Liquids, 3000 psi-Gases,
Temperatures: 10°C to 135°C

LA-CO INDUSTRIES, INC.
1201 Pratt Boulevard, Elk Grove Village, IL 60007-5746
© 2015 LA-CO Industries, Inc. la-co.com

Distributed by Bromic

BROMIC
PLUMBING & GAS

10 Phiney Place Ingleburn
Sydney NSW 2565 Australia
www.bromic.com.au
AUS: 1300 276 642
NZ: 0508 276 642



9 320688 018182

PART NO. 1711895

236mL