

OXYGEN

COMPRESSED OXYGEN

DANGER:

May cause or intensify fire; oxidizer. Contains gas under pressure; may explode if heated.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep away from clothing and other combustible materials. Keep valves and fittings free from oil and grease. Pressurized container: Do not pierce or burn, even after use. In case of fire: Stop leak if safe to do so. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Keep out of reach of children. Not suitable for medical purposes.

INSTRUCTION FOR USE:

1. This bottle must be used with an approved pressure regulator.
2. Remove the protection cap of the valve.
3. Connect the regulator to the discharge valve.
4. Set the outlet flow/ pressure from the regulator.
5. Avoid shock
6. Use according to MSDS

Dispose the cylinder only once completely empty, in a recycling area.



PW 110 PH 165 BAR 0.95 L

EN ISO 11118:2015 I

0426
T 0426



NON RICARICARE - DO NOT REFILL

Manufacturer:
EUROTRE SRL
Via A. Volta, 12/13
42024 Castelvetro di Sotto
Reggio Emilia - Italy
Phone +390522485054

BROMIC[®]

PLUMBING & GAS

For full range visit www.bromic.com/plumbing

OXYGEN

INDEX 008-001-00-8 CAS N. 7782-44-7

NET VOLUME
Contents: 105 Litre
WP: 110 bar
Fitting: M12x1
W.C.: 950 ml
Net Weight 145 g - 5 oz

OXYGEN

www.bromic.com/plumbing

BROMIC PTY LTD
10 Phiney Place,
INGLEBURN
NSW, 2565
AUSTRALIA

PART NO. 1811320
MADE IN ITALY



UN 1072
OXYGEN COMPRESSED



www.bromic.com/plumbing