

# OXYGEN

# BROMIC<sup>®</sup>

## PLUMBING & GAS

# OXYGEN

### COMPRESSED OXYGEN

#### DANGER:

May cause or intensify fire; oxidiser.

Contains gas under pressure; may explode if heated.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep away from clothing and other combustible materials. Keep valves and fittings free from oil and grease. Pressurized container: Do not pierce or burn, even after use.

In case of fire: Stop leak if safe to do so. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Keep out of reach of children.

Not suitable for medical purposes

#### INSTRUCTION FOR USE:

1. This bottle must be used with an approved Pressure regulator.
2. Remove the protection cap of the valve.
3. Connect the regulator to the discharge valve.
4. Set the outlet flow/ pressure from the regulator.
5. Avoid shock
6. Use according to MSDS

Dispose the cylinder only once completely empty, in a recycling area



PW 116 PH 174 BAR 1.4 L

EN ISO 11118:2015 I 0426 IT

T 0426

**NON RICARICARE - DO NOT REFILL**

For full range visit [www.bromic.com/plumbing](http://www.bromic.com/plumbing)

# OXYGEN

INDEX 008-001-00-8 CAS N. 7782-44-7

### NET VOLUME

Contents: 156 Litre

WP: 110 bar

Fitting: M12x1

W.C.: 1420ml

Net Weight: 220 G

[www.bromic.com/plumbing](http://www.bromic.com/plumbing)

PART NO. 1811321  
MADE IN ITALY

BROMIC PTY LTD  
10 Phiney Place,  
INGLEBURN  
NSW, 2565  
AUSTRALIA



**UN 1072**  
**OXYGEN COMPRESSED**



[www.bromic.com/plumbing](http://www.bromic.com/plumbing)