

BIGGER CYLINDER MORE GAS

BROMIC[®]

PLUMBING & GAS

For full range visit www.bromic.com/plumbing

OXYGEN

INDEX N. 008-001-00-8 CAS N. 7782-44-7

NET VOLUME

Contents: 242 lt
WP 110 bar
Fitting M12X1
W.C. 2200 ml
Net Weight 345 g - 12 oz

OXYGEN

COMPRESSED OXYGEN

May cause or intensify fire; oxidizer. Contains gas under pressure; may explode if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Keep/Store away from clothing and combustible materials. Keep valves and fittings free from oil and grease. Pressurized container:

Do not pierce or burn, even after use. In case of fire: Stop leak if safe to do so. Protect from sunlight. Store in a well-ventilated place.

Do not expose to temperatures exceeding 50°C/122°F.

Keep out of reach of children

Not suitable for medical purposes.

INSTRUCTION FOR USE:

1. This bottle must be used with an approved pressure regulator.
2. Remove the protection cap of the valve.
3. Connect the regulator to the discharge valve.
4. Set the outlet flow/ pressure from the regulator.
5. Avoid shock
6. Use according to MSDS



PW 110 PH 165 BAR 2.2 L

EN ISO 11118:2015 I 0426 IT

T 0426

NON RICARICARE - DO NOT REFILL

Fabbricante
EUROTRE S.r.l.
Via A.Volta, 12/13
42024 Castelnovo di Sotto
(RE) Italy - Tel.
0522/485054

OXYGEN

PART NO. 1811322
MADE IN ITALY

BROMIC PTY LTD
10 Phiney Place,
INGLEBURN
NSW, 2565
AUSTRALIA



9 320688 019332



UN 1072
OXYGEN COMPRESSED



Dispose the cylinder only once completely empty, in a recycling area.

www.bromic.com/plumbing