

BIGGER CYLINDER MORE GAS

BROMIC[®]

PLUMBING & GAS

For full range visit www.bromic.com/plumbing

ARGON

COMPRESSED ARGON

WARNING:

Contains gas under pressure, may explode if heated.

Pressurised container.

Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

Do not pierce or burn, even after use.

Dispose the cylinder only once completely empty in a recycling area.

Do not expose a naked flame or any incandescent material.

Keep out of reach of children

High concentration may cause

asphyxiation. Use only in ventilated area.

INSTRUCTION FOR USE:

1. This bottle must be used with an approved pressure regulator.
2. Remove the protection cap of the valve.
3. Connect the regulator to the discharge valve.
4. Set the outlet flow/ pressure from the regulator.
5. Avoid shock
6. Use according to MSDS



PW 110 PH 165 BAR 2.2 L

EN ISO 11118:2015 I 0426

TT 0426



NON RICARICARE - DO NOT REFILL

Fabbricante
EUROTRE S.r.l.
Via A.Volta, 12/13
42024 Castelnuovo
di Sotto (RE)
Tel. 0522/485054

www.bromic.com/plumbing

ARGON

100% ARGON

CAS NUMBER 7440-37-1
EINECS NUMBER 231-147-0

Code 1811524

Volume 2.2 L

Working Pressure: 110 bar

Net Weight 430 G

Test Pressure 165 bar

Content 242 lt Ar

www.bromic.com/plumbing

ARGON

DO NOT REFILL

NON RECHARGEABLE

DISPOSABLE CYLINDER

PROPERTIES

FORMULA: Ar

VALVE: M10x 1

Distributor:

BROMIC PTY LTD

10 Phiney Place Ingleburn NSW

2565 Australia

AUS: 1300 276 642

NZ : 0508 276 642



UN 1006
ARGON, COMPRESSED



9 320688 019295

www.bromic.com/plumbing