

BROMIC[®]

PLUMBING & GAS

For full range visit www.bromic.com/plumbing

CO₂ - FOOD GRADE

COMPRESSED CO₂

WARNING:

Contains gas under pressure, may explode if heated.
Pressurised container.
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
Do not pierce or burn, even after use.
Dispose the cylinder only once completely empty in a recycling area.
Do not expose a naked flame or any incandescent material.
Keep out of reach of children
High concentration may cause asphyxiation. Use only in ventilated area.

INSTRUCTION FOR USE:

1. This bottle must be used with an approved pressure regulator.
2. Remove the protection cap of the valve.
3. Connect the regulator to the discharge valve.
4. Set the outlet flow/ pressure from the regulator.
5. Avoid shock
6. Use according to MSDS

CO₂

FOOD GRADE

100% CO₂

CAS-No.: 124-38-9 EC-No.: 204-696-9

Code 1811526

Volume 2.2 L

Working Pressure: 110 bar

Test Pressure 165 bar

Content 1,300g CO₂



PW 110 PH 165 BAR 2.2 L

EN ISO 11118:2015 I 0426 IT

TY 0426

NON RICARICARE - DO NOT REFILL

Fabbricante
EUROTRE S.r.l.
Via A.Volta, 12/13
42024 Castelnovo di Sotto
(RE) Italy
Tel. 0522/485054

www.bromic.com/plumbing

CO₂ - FOOD GRADE

DO NOT REFILL

NON RECHARGEABLE

DISPOSABLE CYLINDER

PROPERTIES

FORMULA: CO₂ E290 (FOOD GRADE)

VALVE: M10x1

Distributor:

BROMIC PTY LTD

10 Phiney Place Ingleburn NSW

2565 Australia

AUS: 1300 276 642

NZ : 0508 276 642



UN 1013
CARBON DIOXIDE



ONLY DISPOSE OF COMPLETELY EMPTY CYLINDER.

STEEL Separate components and recycle according to local regulations.



www.bromic.com/plumbing

www.bromic.com/plumbing