

BROMIC[®]

PLUMBING & GAS

For full range visit www.bromic.com/plumbing

NITROGEN

COMPRESSED NITROGEN

WARNING:

Contains gas under pressure, may explode if heated.

Pressurised container.

Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

Do not pierce or burn, even after use.

Dispose the cylinder only once completely empty in a recycling area.

Do not expose a naked flame or any incandescent material.

Keep out of reach of children

High concentration may cause

asphyxiation. Use only in ventilated area.

INSTRUCTION FOR USE:

1. This bottle must be used with an approved pressure regulator.
2. Remove the protection cap of the valve.
3. Connect the regulator to the discharge valve.
4. Set the outlet flow/ pressure from the regulator.
5. Avoid shock
6. Use according to MSDS



Fabbricante
EUROTRE S.r.l.
Via A.Volta, 12/13
42024 Castelnovo
di Sotto (RE)
Tel. 0522/485054



PW 110 PH 165 BAR 2.2 L

EN ISO 11118:2015 I

T 0426

NON RICARICARE - DO NOT REFILL

www.bromic.com/plumbing

NITROGEN

E941 FOODGRADE

REG. CE 852/2004
APPROVAL NR IT AAE 080 13

ITEM 1811527

Volume 2.2 L

Working Pressure: 110 bar

Test Pressure 165 bar

Content 242 lt N₂

Net weight 300 g

www.bromic.com/plumbing

NITROGEN

DO NOT REFILL

NON RECHARGEABLE

DISPOSABLE CYLINDER

PROPERTIES

FORMULA: NITROGEN

VALVE: M10x 1



Distributor:

BROMIC PTY LTD

10 Phiney Place Ingleburn NSW

2565 Australia

AUS: 1300 276 642

NZ : 0508 276 642



**UN 1066
NITROGEN
COMPRESSED**



9 320688 019325



www.bromic.com/plumbing