



Bromic Test Plugs are designed for testing leaks and to seal off sections of pipelines. The Test Plugs are developed with a vent tube for venting excess back-pressure, suitable to test pressure in sewage, waste and stormwater pipes. Before selecting a test plug the maximum allowed back pressure should be pre-determined.

Features

- Available in sizes from 40mm - 150mm
- Thrust washers fitted as standard on all sizes
- Zinc plated - corrosion resistant to 90 hours of salt spray test
- Combines the economy of price with the strength of steel
- Quality guaranteed
- One-person, easy installation

Specifications

Part No.	Internal Nominal Pipe Diameter		Internal Compatible Pipe Size		Minimum Depth (Inserted in pipe)	Plug Length	Waterway Diameter	Max. Back Pressure	Weight
	Metric	Imperial	Minimum	Maximum					
8688000	40mm	1 1/2"	37mm	50mm	31mm	81.5mm	15mm	30psi	0.16kg
8688001	50mm	2"	50mm	61mm	32.7mm	82.8mm	15mm	30psi	0.18kg
8688002	65mm	2 1/2"	61mm	75mm	33.2mm	80.5mm	15mm	30psi	0.26kg
8688003	75mm	3"	73mm	85mm	34mm	80.5mm	15mm	20psi	0.28kg
8688004	100mm	4"	94mm	108mm	37.5mm	83.3mm	15mm	10psi	0.41kg
8688005	150mm	6"	150mm	160mm	39.7mm	83.3mm	15mm	10psi	0.75kg