

- Prevents heat damage to components during soldering, brazing or welding.
- The unique gelled formula sticks to the surface without drips and runs.
- Protects adjoining areas made of wood, wallboard, insulation, etc.
- No messy cleanup.



LA-CO® Heat Barrier Spray

Cool Gel®

Directions: Shake well . Spray Cool Gel on surface to be protected from heat source. Be sure surface is completely covered with Cool Gel. Spray on immediately before applying heat source. Reapply Cool Gel as needed to complete job . Do not freeze. For industrial use only. Keep out of reach of children.



Made in U.S.A.

LA-CO®

LA-CO Industries, Inc.
1201 Pratt Blvd.
Elk Grove Village, IL 60007
www.laco.com

Distributed by Bromic

BROMIC
PLUMBING & GAS

10 Phiney Place Ingleburn
Sydney NSW 2565 Australia
www.bromic.com.au
AUS : 1300 276 642
NZ: 0508 276 642

Not WHMIS Controlled
© 2011 LA-CO Industries, Inc.



9 320688 018014

Part No. 1711810
PP52R00327

- Protects Heat Sensitive Components
- No Drip Formula
- Non-corrosive
- Non-toxic
- No Cleanup
- Non-staining

Stays Where It's Sprayed



Net Wt. 16 Fl. Oz. (1 Pt.) .473 Liter