



Features

Made from next-generation materials and precision construction, FlexPro™ delivers industry-leading flexibility, temperature tolerance and chemical resistance which means you can count on it even in the toughest conditions.

- Reliable performance in both residential and commercial installations
- Long service life with zero risk of internal corrosion or chemical degradation
- Safer and faster installations, ideal for professional plumbers demanding efficiency.
- Environmentally stable materials with resistance to temperature cycling and UV exposure
- Burst Proof, Anti-Corrosion & Kink Free water hose

Certifications



Specifications

PRODUCT CODES	8WRB0225	8WRB0300	8WRB0450	8WRB0600
Barcode / GTIN	9320688427236	9320688427243	9320688427250	9320688427267
Hose Length (mm)	225mm	300mm	450mm	600mm
Application	Residential and commercial hot and cold water applications.			
Warranty	15 Years			
Diameter(mm)	8mm			
Watermark Certified	AS 3499			
Max. Working Pressure	1400 kPa			
Max. Heated Water / Working Temperature (°C)	90°C @ 1400 kPa			
Max. Cold Water Supplies	5°C @ 1400 kPa			
Water Hose Class	Class 2			
Temperature Range, °C	5°C to 90°C ([H] High Temperature)			
Brands	Bromic			
Fuel Type	Potable/drinking water			
Material	Nylon anti-corrosion braiding (ACB)			
Thread Size	1/2"			
Connector	FC			
Inner Core	PE-RT			
Connection Type	Straight			

As tested on Bolt M 10x20 – quality 8.8. – Nut h – 0.8d. Approved to 2000 kPa.

V3 03/2026

FLEXPRO WATER HOSE

Kink Free



Features

Made from next-generation materials and precision construction, FlexPro™ Elbow connector delivers industry-leading flexibility, temperature tolerance and chemical resistance which means you can count on it even in the toughest conditions.

- Reliable performance in both residential and commercial installations
- Long service life with zero risk of internal corrosion or chemical degradation
- Safer and faster installations, ideal for professional plumbers demanding efficiency.
- Environmentally stable materials with resistance to temperature cycling and UV exposure
- Burst Proof, Anti-Corrosion & Kink Free water hose

Certifications



Specifications

PRODUCT CODES	E8WRB0225	E8WRB0300	E8WRB0450
Barcode / GTIN	9320688427472	9320688218100	9320688428356
Hose Length (mm)	225mm	300mm	450mm
Application	Residential and commercial hot and cold water applications.		
Warranty	15 Years		
Diameter(mm)	8mm		
Watermark Certified	AS 3499		
Max. Working Pressure	1400 kPa		
Max. Heated Water / Working Temperature (°C)	90°C @ 1400 kPa		
Max. Cold Water Supplies	5°C @ 1400 kPa		
Water Hose Class	Class 2		
Temperature Range, °C	5°C to 90°C ([H] High Temperature)		
Brands	Bromic		
Fuel Type	Potable/drinking water		
Material	Nylon anti-corrosion braiding (ACB)		
Thread Size	1/2"		
Connector	F		
Connection Type	Elbow		
Inner Core	PE-RT		



Features

Made from next-generation materials and precision construction, FlexPro™ M&F Pair delivers industry-leading flexibility, temperature tolerance and chemical resistance which means you can count on it even in the toughest conditions.

- Pair comes with 2x 1/2" G F x 1/2" G M Hoses suitable for hot and cold water mixer tap extension
- Reliable performance in both residential and commercial installations
- Long service life with zero risk of internal corrosion or chemical degradation
- Safer and faster installations, ideal for professional plumbers demanding efficiency.
- Environmentally stable materials with resistance to temperature cycling and UV exposure
- Burst Proof, Anti-Corrosion & Kink Free water hose

Certifications



Specifications

PRODUCT CODES	8WRF0150-P	8WRF0225-P
Barcode / GTIN	9320688428370	9320688428363
Hose Length (mm)	150mm	225mm
Application	Residential and commercial hot and cold water applications.	
Warranty	15 Years	
Diameter(mm)	8mm	
Watermark Certified	AS 3499	
Max. Working Pressure	1400 kPa	
Max. Heated Water / Working Temperature (°C)	90°C @ 1400 kPa	
Max. Cold Water Supplies	5°C @ 1400 kPa	
Water Hose Class	Class 2	
Temperature Range, °C	5°C to 90°C ([H] High Temperature)	
Brands	Bromic	
Fuel Type	Potable/drinking water	
Material	Nylon anti-corrosion braiding (ACB)	
Thread Size	1/2"	
Connector	F & M	
Connection Type	Mixer Tap	
Inner Core	PE-RT	